



**Notes:**

Doc's® TCS - Temporary Cable Supports: Specially designed as a reusable, temporary support to keep cables & cords off the ground. Install & uninstall from the ground using the Quic Stic telescoping pole tool. High Performance Hybrid J Hook. TIA 569-D Compliant with an optimum bend tested and certified by Q-PLUS Laboratories in Irvine, CA 92618. An ISO 9001 registered / ISO 17025 accredited independent lab. Load rating is based on a 3 to 1 safety factor. Ultimate Load rating is to failure point.

Material	Steel / Polypropylene
Finish	Eco-friendly Zinc Cr3+ & Silver Zinc
Origin	Designed & assembled in California, Made in China
Load Rating	See chart above
Ultimate Load	See chart above
Certification	Q-Plus, Plenum Rated, TIA Compliant
Pkg. Qty.	1 EA
UPC	See chart above

Part No.	J-Hook Size	Load Rating	Color	Description	H	L
TCS-HPH16-12	1"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	3.5"	12"
TCS-HPH16-24	1"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	3.5"	24"
TCS-HPH16-36	1"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	3.5"	36"
TCS-HPH32-12	2"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	4.5"	12"
TCS-HPH32-24	2"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	4.5"	24"
TCS-HPH32-36	2"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	4.5"	36"
TCS-HPH48-12	3"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	6.5"	12"
TCS-HPH48-24	3"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	6.5"	24"
TCS-HPH48-36	3"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	6.5"	36"
TCS-HPH64-12	4"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	7"	12"
TCS-HPH64-24	4"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	7"	24"
TCS-HPH64-36	4"	20 lbs.	White	HPH J-Hook assembled to 3" dia. grappling hook	7"	36"

Contact us for additional color part numbers

	<b>Plenum Rated</b> <b>TIA Compliant</b>				
			Doc's Industries, Inc. 4121 Guardian St. Simi Valley, CA 93063 www.docindustries.com Phone: 800-544-8706		
<b>Cable Capacity</b>					
Part No.	Area	Dia.	CAT 5e	CAT 6	CAT 6a
HPH16	1.29 in <sup>2</sup>	1"	20	15	10
HPH32	3.89 in <sup>2</sup>	2"	90	60	35
HPH48	8.37 in <sup>2</sup>	3"	200	150	80
HPH64	15.08 in <sup>2</sup>	4"	330	220	140
<b>Part Number: See Chart Above</b>			<b>Title: Temporary Cable Support with 1", 2", 3" or 4" HPH J-Hook &amp; 3" diameter grappling hook. Available in 12", 24" or 36" overall lengths. HPH Hooks available in white, red, black &amp; blue.</b>		
<b>Date: 3/3/2020</b>			<b>Drawn by: RO</b>		
<b>Drawing Number: 11533P</b>			<b>Sheet 1 of 1</b>		